

## LA-UR-19-32722

Approved for public release; distribution is unlimited.

Title: Thermochemical and Thermophysical properties for the system of Ce metal and Ce hydride (deuteride)

Author(s): Schulze, Roland K.

Intended for: support information for LDRD project  
Report

Issued: 2019-12-23

---

**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

# Thermochemical and Thermophysical properties for the system of Ce metal and Ce hydride (deuteride)

Roland K. Schulze

Los Alamos National Laboratory

Los Alamos, NM 87545

rkschulze@lanl.gov


- Knowledge of these properties is necessary in order to properly build a physics based model of the Ce ejecta evolution (conversion) in high pressure hydrogen gas
- Experimental measurements and corroboration with theory
- Knowledge of properties across phase space of the dynamic experiments:
  - Temperatures up to 1500K + if possible
  - Gas pressures from vacuum to ~ 8 atm (~100 atm in shocked condition)

## Properties desired as a function of temperature

- Ce – hydrogen –  $\text{CeH}_x$  phase diagram at higher temperatures
- Ce and  $\text{CeH}_2$  heat capacity (specific heat)
- Ce and  $\text{CeH}_2$  thermal conductivity
- Ce and  $\text{CeH}_2$  coefficient of thermal expansion (CTE)
- Reaction enthalpy  $\text{Ce} + \text{H}_2 \rightarrow \text{CeH}_{2+x}$ ,  $\Delta H = 206 \text{ kJ/mol}$
- $\text{CeH}_2$  melting temperature
- $\text{CeH}_2$  optical emissivity
- Diffusion of H in  $\text{CeH}_{2+x}$
- Reaction rates  $\text{Ce} + \text{H}_2 \rightarrow \text{CeH}_{2+x}$
- Mechanical properties of  $\text{CeH}_2$

Hypothesis: reactive conversion


$\text{Ce} + \text{H}_2 \rightarrow \text{CeH}_{2+x}$   $\rightarrow$  other processes leading to particle breakup



liquid Ce > 1071K



$\delta$ -Ce > 999K bcc

$\gamma$ -Ce > 263K fcc




$\text{CeH}_2$

Fluorite crystal structure unit cell of  $\text{CeH}_2$ . Blue spheres represent Ce and orange spheres H. For the dihydride, all the tetrahedral sites in the FCC base Ce lattice are fully occupied, and for the higher ( $\text{CeH}_{2+x}$ ) stoichiometries, the octahedral sites become occupied.



# Conceptual view of the early stage of hydriding

$$f = \frac{P}{\sqrt{2\pi M k T}}$$





- Gas delivery (kinetic gas theory)
- Transport of reactant to interface (hydrogen diffusion)
- Reaction at interface  $\text{Ce} + 2\text{D} \rightarrow \text{CeD}_2 + \Delta H_f$
- Reaction kinetics  $\text{Ce} + 2\text{D} \rightarrow \text{CeD}_2$
- Exothermic heat generation  $\Delta H_f = -206 \text{ kJ/mol}$
- Heat flow into Ce metal center:  $C_p(\text{Ce}), K(\text{Ce})$
- Heat flow into  $\text{CeD}_2$  skin:  $C_p(\text{CeD}_2), K(\text{CeD}_2)$
- Heat partition into gas:  $C_p(\text{D}_2), K(\text{D}_2)$

Conversion process:  
parameters needed for model

## Possible other factors



- Reaction volumetric change +26%
- Melting temperature of  $\text{CeD}_2$
- CTE for Ce and  $\text{CeD}_2$
- Mechanical properties of hydride




F.D. Manchester and J.M. Pitre, The Ce-H (Cerium-Hydrogen) System, Phase Diagram Evaluations: Section II, J. Phase Equil. Vol. 18 No. 1, 1977, 63-77.

$\epsilon$  is the  $\text{CeD}_{2+x}$  phase. This phase is stable in the two phase field from  $\text{D/Ce}=0.2$  and higher. The  $\epsilon$  phase is stable at higher temperatures from  $\text{D/Ce} \approx 1.8$  to  $\approx 2.8$ , where the trihydride forms. Note that the  $\text{CeD}_2$  phase remains solid under the right  $\text{D}_2$  pressure conditions to at least  $1200^\circ\text{C}$  ( $1473\text{K}$ ). It is important that we determine the melting temperature of  $\text{CeD}_2$ . Melting point might be in excess of  $2000\text{K}$  based on similar structure Ce compounds ( $\text{CeO}_2$ ).

# Conversion process: Thermal stability of hydride product



# Conversion process: Thermal stability of hydride product





# Conversion process: Thermal stability of hydride product

- The unary P-T phase diagram of  $\text{CeH}_2$
- The  $\text{CeH}_2$  P-T stability line (extrapolated from data) becomes the boundary between  $\text{CeH}_2$  solid and vapor phases and the  $\text{CeH}_2$  liquid and vapor phases. This makes sense since the once the  $\text{CeH}_2$  is no longer stable (loss of hydrogen and conversion towards Ce metal liquid) the temperature is high enough to cause vaporization of the Ce.
- The triple point is estimated using the melting point of  $\text{CeF}_2$  at 1710K
  - $\text{CeF}_2$  is has the same crystal habit (structurally identical) as  $\text{CeH}_2$
  - $\text{CeF}_2$  is isoelectronic to  $\text{CeH}_2$  – the configuration is  $(\text{Ce}^{3+}, 2\text{H}^-, \text{e}^-)$  which leads to a metallic-behavior hydride
- I don't know the direction/shape of the  $\text{CeH}_2$  solid – liquid boundary (most likely more vertical than I have it drawn)
- $\Delta H_{\text{sublimation}} > 0$  endothermic (will cool the system)
- $\Delta H_{\text{fusion}} > 0$  endothermic (will cool the system)
- $\Delta H_{\text{vaporization}} > 0$  endothermic (will cool the system)
- $\Delta H_{\text{sublimation}} = \Delta H_{\text{fusion}} + \Delta H_{\text{vaporization}}$
- For Ce metal  $\Delta H_{\text{sublimation}} = 420 \text{ kJ/mol}$  literature value
- The process of  $\text{CeH}_{2(s)} \rightarrow \text{Ce} \cdots \text{H}_{2(g)}$  can be broken down as:
  - $\text{CeH}_{2(s)} \rightarrow \text{Ce}_{(s)} + \text{H}_{2(g)} + 206 \text{ kJ/mol}$
  - $\text{Ce}_{(s)} \rightarrow \text{Ce}_{(g)} + 420 \text{ kJ/mol}$
  - Total maximum of 626 kJ/mol possible required for the sublimation process of  $\text{CeH}_2$  depending on what the final gas phase products are ( $\text{CeH}_{2(g)}$  or  $\text{Ce}_{(g)}$  and  $\text{H}_{2(g)}$ ) – cooling power
  - Regardless of the nature of the gas phase products this would definitely be (atomic/molecular) and couple to the gas